



Technical data Hankook

Dimension	Compound	Diameter	Section Width Overall	Circumference Static
215/615R 17	Medium	613	240	1925
215/615R 17	Hard	613	240	1925
235/620R 17	Medium	615	252	1932
240/640 R 18	Medium	644	245	2023
240/640 R 18	Hard	644	245	2023
260/660 R 18	Medium	660	282	2073
270/680 R 18	Medium	685	298	2152
280/650 R 18	Medium	654	306	2055
280/660 R 18	Medium	662	304	2080
280/680 R 18	Medium	680	306	2136
300/660 R 18	Medium	654	330	2055
280/710 R 18	Medium	710	306	2231
300/680 R 18	Medium	680	328	2136
320/710 R 18	Medium	706	346	2218
320/710 R 19	Medium	706	348	2218

Hankook Tyre Dimension's and technical data's

Tyre pressure target:	Cold pressure front	Cold pressure rear:	Hot pressure front:	Hot pressure rear: Front
Front wheel drive:	1,5 – 1,6 bar	1,7 – 1,8 bar	2,0 – 2,2 bar	2,2 – 2,4 bar
Rear wheel drive:	1,4 – 1,5 bar	1,3 – 1,4 bar	1,9 – 2,0 bar	1,8 – 1,9 bar

- WET Tyre: Generally 0,2 bar higher (cold pressure)

Camber

Front axle	max. 4° 00'
Rear axle	max: 3° 30'